



Tooling solutions for the power utility industry.



60, 100 & 200 TON COMPRESSION HEADS

RELIABLE - MODEL EP-60D

The EP-60D double-acting, 60 ton press is designed to compress sleeves and lugs on ACSR and ACAR transmission and distribution cables. Operable from any 10,000 psi pumping source, these tools are made to be portable for easy maneuverability. Accepts any shell type dies currently used with Alcoa or Burndy 60 ton presses. Double acting feature eliminates the possibility of jamming or connector hang up.

EP-60DT (Titanium) 40% lighter than model above.

RELIABLE - EP-100WB & EP-200WA

The EP-100WB and EP-200WA are 100 and 200 ton compression heads for full tension, transmission and substation connections.

The **EP-100WB** will accept shell type dies currently used with Alcoa 100 ton compression heads. 200 ton dies are considered special application and must be engineered to the connector manufacturer's specifications. Consult factory for these dies.

These compression heads are double-acting, and designed to operate from the REL 554, PPE 1020, REL-10-I or any 3/4 hp, high-pressure, double-acting pump with the proper oil capacity.



FEATURES:

- ✓ **Lightweight**
- ✓ **Removable die cap for easy connector positioning.**
- ✓ **Tool stand included (EP-60D)**
- ✓ **3/8" Screw-type couplers**
- ✓ **Carrying case included (EP-60D)**



MODEL	EP-60D	EP-100WB	EP-200WA
Output	60 ton	100 ton	200 ton
Weight	47 lbs.	96 lbs.	190 lbs.
(Titanium)	34 lbs.	N/A	N/A
Size	5"W x 17"H	7-1/2"W x 14"H	14"W x 17"H
Ram Stroke	1.5" travel	.98" travel	1.57" travel
Oil Capacity	303 cc	314 cc	1134 cc

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193