



SPERRY PSI-8031 - PHASE SEQUENCE AND OPEN PHASE INDICATOR

PSI-8031



Meets CE Requirements

This palm-size lightweight unit features a broad operating range and an easy to read display. The shock resistant plastic housing (no exposed metal parts), 60" line cord and color coded insulators over alligator clips enhance safety for the user and the unit.

One Year Limited Warranty

SPECIFICATIONS	
Voltage	600V on 3-Phase Power Source
Duty Cycle	Continuous to 500V 5 Min. Max. From 500V to 600V
Frequency	50-60Hz
Insul. Test	2,200 VAC for 1 min.
Dimensions	4.24" H x 3" W x 1.6" D
Weight	12.5 oz.

C-31 - CARRYING POUCH (INCLUDED)

SPR-300-PLUS



UL Listed
Meets CE Requirements

SNAP 8 PLUS SERIES UL LISTED SNAP-AROUNDS

These units feature broad frequency response (50-400Hz), recessed terminals, large optically clear window, Ohm scale on dial drum, range finder symbols, pointer lock, insulated industry standard safety test leads, tapered jaws, safety wrist strap, and lifetime limited warranty.

The SPR-300 PLUS comes packed with TL-52 Test Leads, (1) F-1 Fuse *installed*, (1) Spare *in back cover*, (1) B-1 Fuse Battery "AA" type 1.5V, Operating Instructions and Warranty Card.

SPECIFICATIONS	
Frequency	SPR-300 PLUS.
Response	500-400Hz
Duty Cycle	Continuous
Max. Conductor	1.2"
Fuse Protection	#F-1 - 1/2A 250V fast acting High Interrupting capacity 1/4" x 1-1/4" Fuse.
Power Supply	#B-1 - 1.5V AA battery
Dimensions	8.7" H x 3.3" W x 1.6" D
Weight	13.8 oz.

NOTE

Instrument designed for current readings on circuits with a maximum of 600VAC.

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193