



Tooling solutions for the power utility industry.



LR-88.5 - HYDRAULIC LONG REACH CHAINSAW

The LR-88.5 is intended for safe cutting and trimming of trees and limbs up to 13 inches in diameter, from the ground or an aerial bucket, that would be out of reach for traditional chainsaws.

Features:

88.5 inch overall length.

Insulated fiberglass extension tube - reduce risk of electrical shock when used near an energized line.

Meets OSHA 1910.269

Automatic Chain Oiler - provides continuous lubrication to the chain and guide bar while the saw is running, minimizing wear and extending tool life.

Trigger Guard - will prevent accidental chain movement.

Covered Sprocket Guard.

Rubber Collar Hand Stop.

Quick Set Spool - may be turned 180° for open- or closed-center operations.

15" Bar - Allows a 13" cutting capacity.

SPECIFICATIONS:

Cutting Capacity: 13 in.

Weight: 9.5 lbs.

Flow Range: 5-8 gpm

Cutting Chain @ 8gpm: 4,200 fpm/min.

Operating Pressure: 1,000-2,000 psi

Pressure and Return Port Thread: 3/8" NPTF

Chain Size: .325 in. pitch

Chain Gauge: .058 in.

Hoses and fittings used with this tool must comply with S.A.E. J1273 which covers recommended practice for selection, installation and maintenance of hose and hose assemblies.

Failure to comply with all warnings could result in severe bodily injury.

The correct hoses and fittings are available from **Reliable Equipment**. Consult your representative when ordering to ensure compliance with all safety requirements.

**IF YOU DON'T SEE WHAT YOU NEED
CONTACT RELIABLE EQUIPMENT
800-966-3530**

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193