



Tooling solutions for the power utility industry.

POLE TAMPERS

Makes quick work of setting poles, asphalt patch and general construction backfill compacting.

Only 3 moving parts for low maintenance.

Reversible On/Off valve for Open- and Closed-Center systems (hose-end models).

Standard with kidney-shaped foot.

Rotate trigger spool for Open- and Closed-Center systems (valve on tube models).

TAMPER - HOSE END VALVE

H4802 Pole Tamper - length 60", 23 lbs.

H4802-1 Pole Tamper - length 85", 28 lbs.

43227 Pole Tamper - length 85", 28 lbs.
28 lb. - unit does not include on/off valve

H4802-6 Pole Tamper - length 60", 27 lb.
27 lb. - unit does not include on/off valve

TAMPER - VALVE ON TUBE

H4802-3 Pole Tamper - length 72", 23 lbs.
2.5" x 8" kidney shaped foot

H4802-5 Pole Tamper - length 60", 22 lbs.
2.5" x 8" kidney shaped foot

48383 Pole Tamper - length 72", 23 lbs.
4" x 8-3/16" rectangular foot



SPECIFICATIONS:

Width: 4"

Flow Range: 4-6 gpm

Operating Pressure: 1,000-2,000 psi

Pressure Port Thread: 9/16-18 SAE O-Ring

Return Port Thread: 3/4-16 SAE O-Ring

Standard Foot Size: 2.5 x 8" kidney-shaped

Blows Per Minute: 1,160 @ 5 gpm

POLE TAMPER ACCESSORIES

114255	Round Foot - 6"	FOR USE WITH ALL MODELS LISTED ABOVE
114256	Rectangular Foot - 4 x 8-13/16 in.	
111964K	Kidney Shaped Foot	

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193