



RELIABLE - REL-2250 & REL-2250-O HYDRAULIC HOSE

Low pressure rubber hoses designed and tested to meet the electrical conductivity requirements established in the utility market. These assemblies are many times more flexible than plastic alternatives. Built to meet the demands of the electric utility industry.

FEATURES: Certified non-conductive, 2,250 psi working pressure, double rayon braid, extreme flexibility (even in cold temperatures). Tested and marked to have passed a total hazard current test of 75kv for 3 min. with current not exceeding 100 micro amps/ foot.

PART (RED)	PART (ORANGE)	PART (RED)	PART (ORANGE)	DESCRIPTION
REL-2250-18-A	REL-2250-O-18-A	REL-2250-18-B	REL-2250-O-18-B	18" Whip Assembly
REL-2250-96-A	REL-2250-O-96-A	REL-2250-96-B	REL-2250-O-96-B	8' Assembly
REL-2250-120-A	REL-2250-O-120-A	REL-2250-120-B	REL-2250-O-120-B	10' Assembly
REL-2250-300-A	REL-2250-O-300-A	REL-2250-300-B	REL-2250-O-300-B	25' Assembly

Each assembly above followed by an "A" includes two 3/8" I.D. hoses with 3/8" NPTF fittings on each end.
 Each assembly above followed by a "B" includes two 3/8" I.D. hoses with 3/8" NPTF male fittings on one hose and 1/2" NPTF male fitting on the other hose.

LOW PRESSURE COUPLINGS

Reliable Equipment stocks a large inventory of low pressure couplings to fit most applications. Contact your Reliable representative for additional selections.



PART	BODY	THREAD	DIMENSIONS			
			Overall	Hex	Dia.	
COUPLERS						
NS-371-6FP	3/8"	3/8-18 NPSF	2.10"	1.06"	1.13"	
FF-371-6FP	3/8"	3/8-18 NPSF	2.39"	1.06"	1.20"	
107956	3/8"	9/16"-18 SAE O-RING external thread	Use with 107957			
		3/4"-16 SAE O-RING external thread				
NIPPLES			Overall	Exposed	Hex	Dia.
NS-372-6FP	3/8"	3/8-18 NPSF	1.70"	1.17"	0.94"	1.08"
FF-372-6FP	3/8"	3/8-18 NPSF	2.31"	1.71"	0.94"	1.08"
107957	3/8"	3/8" NPTF internal thread	Use with 107956			
		1/2" NPTF internal thread				

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193