



Tooling solutions for the power utility industry.



Kit Includes:
1 Battery Powered Tool
1 Carrying Strap
1 Carrying Case
2 BP-70R Batteries
1 CH-3TR 15 Min. AC Charger

Crimping Est.	BP-70I	BP-250RI
#6 CU/AL	145	455
1/0 CU/AL	107	335
4/0 CU/AL	85	265

REC - 358U ROBO* CRIMP™

6 Ton Battery Powered Compression Tool

Designed to squeeze commonly used service entrance connectors, lugs, sleeves, H and C-taps. Easily carried and used in limited access areas because of its swivel head and compact design. Six ton output is equal to any comparable hand-held hydraulic compression tool and far exceeds any mechanical crimper.

A built-in, pre-set 10,000 psi bypass cartridge assures a complete compression every time. The unit accepts either "W" type or "O" type dies. The "D3" nest die comes standard with the tool.

REC-358UN Insulated head standard kit
REC-358UCH Cutter head standard kit

Specifications:

Weight: 8 lbs. w/ Battery
Size: 13" x 12" x 3"
Connector Range:
Lugs & Splices #6 - 4/0 CU/AL
H - Taps 4/0
Cutting Capacities: 500 MCM CU
 1" AL Max. O.D. - 750 MCM bare



Kit includes:
1 Battery Powered Tool
1 Carrying Strap
1 Carrying Case
2 BP-70R Batteries
1 CH-3TR 15 Min. AC Charger

Crimping Est.	BP-70I	BP-250RI
336 ACSR	30	90
795 ACSR	25	75

REC - 3510 ROBO* CRIMP™

12 Ton Battery Powered Compression Tool

The 1.65" jaw opening is the largest in this line. The tool accepts all "U" type dies on the market. A built-in, pre-set 10,000 psi bypass cartridge will audibly kick out when the 12 ton pressure is achieved. The output pressure can be adjusted via a bypass port located at the top of the tool. This tool has the most universal range of all the self-contained ROBO*s.

There is no tool set-up time or extra power source needed. One finger trigger operation nearly eliminates fatigue and muscle related strains. Safer work habits result from using these tools.

Specifications:

Weight: 20 lbs. w/ Battery
Size: 19" x 3.5" x 10.5"
Connector Range:
Lugs & Splices 750 MCM CU/AL

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193



Tooling solutions for the power utility industry.

REC-630 ROBO* CRIMP™

Battery Powered Dieless Crimping Tool 6.2 Ton, .91" Jaw Opening, 1.25" Center

Designed to compress Anderson style lugs. Six tons of compression force are achieved when the tool advances and bypasses at the pre-determined pressure. Advance and retract buttons on the tool handle allow for one hand operation, freeing the other hand to maneuver the cable.

The REC-630 is designed to crimp Anderson style connectors. Other brand connectors manufactured to ANSI specification C119.4 can be used. The cable must be the maximum size specified for the connector. Consult your connector manufacturer for dieless applications.

REC-630N Insulated head standard kit

Specifications:

Weight: 11.5 lbs. w/ Battery
Size: 14" x 13" x 2.5"
Connector Range:
Lugs & Splices 10 AWG-500 MCM



Kit Includes:

1 Battery Powered Tool
1 Carrying Strap
1 Carrying Case
2 BP-70R Batteries
1 CH-3TR 15 Min. AC Charger

Crimping Est.	BP-70I	BP-250RI
1/0 CU/AL	50	150
500 MCM	60	180

REC-750 ROBO^R CRIMP™

Battery Powered Dieless Crimping Tool 6.2 Ton, 1.5" Jaw Opening, 1.5" Center

The dieless system is used for non-tension splices and terminations. There are one stationary and three movable indenting nibs which close at 90° angles to each other so that the connector is squeezed equally at four strategic points. The top can be unlatched to accommodate larger size lugs and cables. Typical applications include in-line splicing, connectors, lug, and terminations.

The REC-705 is designed to crimp Anderson style connectors. Other connectors manufactured to ANSI specification C119.4 can be used. The cable must be the maximum size specified for the connector. Consult your connector manufacturer for dieless applications.

Specifications:

Weight: 12 lbs. w/ Battery
Size: 14" x 13" x 2.5"
Connector Range: #6 AWG - 750 MCM



Flip-Top Model

Kit Includes:

1 Battery Powered Tool
1 Carrying Strap
1 Carrying Case
2 BP-70R Batteries
1 CH-3TR 15 Min. AC Charger

Crimping Est.	BP-70I	BP-250RI
1/0 CU/AL	50	150
500 MCM	60	180

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193