



*Tooling solutions for the power utility industry.*

## **PPE-1020 - ELECTRIC / HYDRAULIC PUMP**

Operate both single- and double-acting tools from this 1/2 hp, 6.5 amp @ 120 VAC pump unit provides up to 10,000 psi hydraulic power for high-pressure cutting and crimping tools.

This compact unit allows use of double-acting cutting and crimping tools in construction situations where hydraulic systems may not be available. Features a built-in relief valve and high-pressure couplers.

**SPECIFICATIONS:** System: Open-Center, Reservoir Capacity: 0.5 gal., Relief Valve Setting 10,000 psi, Output Flow @ 10,000 psi is 18.8 in. 3/min., Fast Advance Flow 0.7 gpm, Weight: 28 lb., 9.5" O.A.L., Width: 7.5", Height: 15.5", H/P Port 1/4-18 NPSM



## **GASOLINE POWERED / HYDRAULIC PUMPS**

### **10-GM**

**4 hp four-cycle gasoline engine**

**Three-stage pump for rapid (2) ram advance**

**3-way valve for single acting operation**

**10,000 psi high-pressure pump**

**Selector for single or double acting mode (4-way option)**

**High-pressure safety relief valve**

**Carrying handle**

**Factory filled oil reservoir**

**Pressure matched quick-coupler(s) supplied**

**Optional:** Operating pressures, 4-way manual valve for double acting operation, and carrying case.



### **30-GS-4**

**7 hp four-cycle gasoline engine**

**Two-stage pump for rapid ram advance**

**10,000 psi high-pressure pump**

**4-way Solenoid valve with remote hand control with 8 foot cord**

**Selector Valve for single or double acting modes**

**High-pressure safety relief valve**

**Protective carrying frame**

**Factory filled oil reservoir**

**Pressure matched quick-couplers supplied**

**Optional:** Operating pressures, 4-way manual valve for double acting operation, and remote foot control.



**TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193**