

RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974 • Phone: 800-966-3530 • Fax: 215-357-9193

GROUNDING CLAMPS AVAILABLE FROM RELIABLE EQUIPMENT



R-GC-2.5A

"C" TYPE (THREADED)

Smooth Jaws
Capacity: .16-2.4" #6-2" IPS
Current: 400 RMS Amps / 60 Hz
ASTM: Type I / Class A / Grade 5H
Compare to: (Closest Match)

Salisbury # 1923

Aluminum Body



R-BGC-1.25

"C" TYPE (THREADED)

Bronze Body Smooth Jaws

Capacity: .16-1.25" # 6-1033 KCM ACSR Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class A / Grade 5 Compare to: (Closest Match)

Salisbury # 1897 Chance # C600-2271



R-GC-2A or 2B (SHOWN)

"C" TYPE (THREADED)

Aluminum Body

(A) Smooth Jaws (B) Serrated Jaws Capacity: .16-2" #6-3000 KCM ACSR Current: 400 RMS Amps / 60 Hz ASTM:

Type I / Class B / Grade 5H

(See also R-GC-2AC & 2BC models)

Compare to: (Closest Match)

Salisbury # 20882 **Chance** # **T600-0658 Hastings** # **10375**



R-BGC-.81

"C" TYPE (DRILLED)

Bronze Body Smooth Jaws

Capacity: .16-.81" # 6-477 KCM ACSR Current: 250 RMS Amps / 60 Hz ASTM: Type I / Class A / Grade 2 Compare to: (Closest Match)

Chance # T600-0465



R-GC-1002

"C" TYPE (THREADED)

Aluminum Body Serrated Jaws

Capacity: .16-1.5" #6-1431 KCMACSR

Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class B / Grade 5

Compare to: (Closest Match)

Salisbury # 1895 Chance # T600-2708 Hastings # 21575



R-BFC-1.5

FLAT (THREADED)

Bronze Body Serrated Jaws Capacity: .112-1.5"

Current: 400 RMS Amps / 60 Hz ASTM: Type III / Class B / Grade 5

Compare to: (Closest Match)
Chance # C600-2231
Hastings #21608



R-FC-1007

FLAT (THREADED)

Aluminum Body Serrated Jaws

Capacity: .06-1.5" Flat or Square Current: 400 RMS Amps / 60 Hz ASTM: Type III / Class B / Grade 5

Compare to: (Closest Match)

Salisbury # 4345



R-FC-1006

FLAT (THREADED)

Bronze Body Serrated Jaws

Capacity: .06-1.5" Flat or Square Current: 300 RMS Amps / 60 Hz ASTM: Type III / Class B / Grade 3 (See also R-FC-1006E w/ Eye Screw)

Compare to: (Closest Match)

Salisbury # 1814

RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974 • Phone: 800-966-3530 • Fax: 215-357-9193

GROUNDING CLAMPS AVAILABLE FROM RELIABLE EQUIPMENT



R-DB-1003

DUCK BILL (THREADED)

Aluminum Body, Serrated Jaw Cap: .16-1.66" # 6-1590 MCM ACSR Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class B / Grade 5 Compare to: (Closest Match) Salisbury # 1853 Chance # C600-0197




DUCK BILL (THREADED)

Aluminum Body Smooth Jaws

Cap: .16-1.1" # 6-795 KCM ACSR Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class A / Grade 5 Compare to: (Closest Match)

Salisbury #21030 Chance # C600-1734 **Hastings # 10476**



DUCK BILL (PRESSURE)

Aluminum Body, Smooth Jaws Cap: .16-1.1" # 6-795 KCM ACSR Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class A / Grade 3 Compare to: (Closest Match) Salisbury # 24404

Chance # G3622-1 **Hastings # 10478**

R-BS-GC

Ball Socket Clamp (THREADED)

ASTM Type I • Class A • Grade 5 Bronze Body 1" Ball Diameter Current: 400 Amps /60 Hz Compare to: (Closest Match) **Salisbury # 21190**

Chance # C600-2101







R-BS-S









RFI -BUS-6.62


"C" TYPE (THREADED)

Aluminum Body Smooth, Flat Lower Jaw For Substation Buses - Round. Square, Rectangle, or "H" Section Capacity: 6.12 IPS 0.4"- 6.62" Current: 400 RMS Amps / 60 Hz ASTM: Type I / Class A / Grade 5

Compare to: (Closest Match) Salisbury # 2991







Copper Plain Ferrule

FFRRUIFS

THREADED PART DIE

R-#2TF 165 R-1/OTF 165 R-2/OTF 165 R-4/OTF 167

PLAIN PART DIE

> R-#2PF 165 R-1/0PF 165 R-2/OPF 165 R-4/0PF 167

R-GR-PS

GROUND PARKING STUD

Style: Bronze Compare to: (Closest Match) Salisbury # 21754

Chance # G3627 **Hastings # 13210**

