

RELIABLE EQUIPMENT & SERVICE CO., INC.

R-CH-12000

MANUALLY LEVER OPERATED 6 TON LINK CHAIN HOIST

The R-CH Series 6 ton hoists promise to provide years of dependable service, under the rigorous conditions demanded by the Power Utility & Line Construction Industries.

The R-CH-12000 feature a time tested and field proven ratchet & pawl design for transmission and distribution applications.

FEATURES:

The ratchet and pawl mechanism provides safe operation in which one pawl is always engaged during lifting and lowering operations.

Cast steel alloy construction provides unmatched resistance to shock and fatigue.

Minimal head & face room required for operation.

May be rigged for use in lifting, pulling or binding applications from any position.

Safety hooks rotate 360° and feature spring latches to provide secure support and load connections.


The compact design is simple to operate and easy to maintain.

Quickly remove slack by pulling the free chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control of the handle.

5 Foot Standard lift.

Custom lift lengths available.



Manufactured to meet
ASME B30.21

R-CH-12000

Rated Capacity:	6 Ton
Approx. Pull:	81 lbs.
Lever Length:	17 in.
Minimum Head Room:	19-1/2 in.
Standard Lift:	53-1/2 in.
Approx. Weight:	46 lbs.



RELIABLE EQUIPMENT

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com