## RELIABLE EQUIPMENT & SERVICE CO., INC.



2" "C" TYPE **GROUND CLAMPS** MADE IN THE U.S.A.

**INTEGRAL** 

### "C" Type Grounding Clamp

ASTM: Grade 5 • ALUMINUM • TYPE I Stainless Steel Eye Screw w/ Fine Threads Tapped for 5/8-11 UNC Ferrule Wt: 2.5 lb.

#### **Grade 5 Electrical Ratings**

Continuous Current 400 (AMPS)

Fault Current - 15 Cycles (AMPS) 43,000 Fault Current - 30 Cycles (AMPS) 30,000

Main Line: Min. - # 6 Sol. Cu. (.162")

Max. - 3000 kcmil (2")

Grade 5H - The R-GC-2A/2B clamps have been tested to meet Grade 5H to support X/R=30 ratio applications, when used with approved 5H rated components, cables, and assemblies.



See reverse for additional options

#### RELIABLEEQUIPMENT&SERVICECO., INC.

Class A • Grade 5/5H

301 Ivyland Road • Warminster, PA 18974 Phone: 800-966-3530 • Fax: 215-357-0363

www.Reliable-Equip.com

# RELIABLE EQUIPMENT & SERVICE CO., INC.



2" "C" TYPE GROUND CLAMPS MADE IN THE U.S.A.



"C" Type Grounding Clamp

**ASTM**: **Grade 5 •** ALUMINUM • TYPE I Stainless Steel Eye Screw w/ Fine Threads Tapped for 5/8-11 UNC Ferrule **Wt: 2.5 lb.** 

**Grade 5 Electrical Ratings** 

Continuous Current 400 (AMPS)

Fault Current - 15 Cycles (AMPS) 43,000 Fault Current - 30 Cycles (AMPS) 30,000

Main Line: Min. - # 6 Sol. Cu. (.162")

Max. - 3000 kcmil (2")

**Grade 5H -** The **R-GC-2AC/2BC** clamps have been tested to meet Grade 5H to support X/R=30 ratio applications, when used with approved 5H rated components, cables, and assemblies.

Smooth Jaw

ASTM TYPE I

Class A • Grade 5H

See reverse for additional options

#### RELIABLEEQUIPMENT&SERVICECO., INC.

301 Ivyland Road • Warminster, PA 18974 Phone: 800-966-3530 • Fax: 215-357-0363

www.Reliable-Equip.com