



RELIABLE EQUIPMENT & SERVICE CO., INC.

2" "C" TYPE GROUND CLAMPS MADE IN THE U.S.A.



R-GC-2BC
Serrated Jaw
ASTM TYPE I
Class B • Grade 5H

THREADED
THROUGH
CONNECTION



R-GC-2AC
Smooth Jaw
ASTM TYPE I
Class A • Grade 5H

"C" Type Grounding Clamp

ASTM: Grade 5H

ALUMINUM • TYPE I

Stainless Steel Eye Screw w/ Fine Threads
Tapped for 5/8-11 UNC Ferrule

Electrical Ratings

Continuous Current 400 (AMPS)

Fault Current - 15 Cycles (AMPS) 43,000

Fault Current - 30 Cycles (AMPS) 30,000

Main Line: Min. - # 6 Sol. Cu. (.162")

Max. - 3000 kcmil (2")

Weight: 2.5 lbs.

RELIABLEEQUIPMENT&SERVICECO.,INC.

301 Ivyland Road • Warminster, PA 18974

Phone: 800-966-3530 • Fax: 215-357-0363

www.Reliable-Equip.com



RELIABLE EQUIPMENT & SERVICE CO., INC.



R-GC-2B
Serrated Jaw
ASTM TYPE I
Class B • Grade 5H

2" "C" TYPE GROUND CLAMPS MADE IN THE U.S.A.

INTEGRAL
BLIND THREAD



R-GC-2A
Smooth Jaw
ASTM TYPE I
Class A • Grade 5H

"C" Type Grounding Clamp

ASTM: Grade 5H

ALUMINUM • TYPE I

Stainless Steel Eye Screw w/ Fine Threads
Tapped for 5/8-11 UNC Ferrule

Electrical Ratings

Continuous Current 400 (AMPS)

Fault Current - 15 Cycles (AMPS) 43,000

Fault Current - 30 Cycles (AMPS) 30,000

Main Line: Min. - # 6 Sol. Cu. (.162")

Max. - 3000 kcmil (2")

Weight: 2.5 lbs.

RELIABLEEQUIPMENT&SERVICECO.,INC.

301 Ivyland Road • Warminster, PA 18974

Phone: 800-966-3530 • Fax: 215-357-0363

www.Reliable-Equip.com