

RELIABLE EQUIPMENT & SERVICE CO., INC.



Manufactured to meet or exceed ASME B30.21.



REL-1500H REL-3000H

MANUALLY LEVER OPERATED ROLLER CHAIN HOIST

These two **NEW** hoists from RELIABLE promise to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industry.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-1500H** has been manufactured to handle a 3/4 ton load with ease.

The **REL-3000H** utilizes a multiple chain configuration to offer a 1-1/2 ton capacity.


The chain lug hook may be detached to provide a longer lift capacity and faster operation in 3/4 ton applications.

Model	REL-1500H	REL-3000H
Capacity:	1,500 lbs.	3,000 lbs.
Travel:	56.5 inches	57 inches
Headroom:	13 inches	15 inches
Handle:	18.75 inches	18.75 inches
Stroke:	27 inches	27 inches
Weight:	18 lbs.	22 lbs.



RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com



RELIABLE EQUIPMENT & SERVICE CO., INC.



R-CH-3000 & R-CH-6000 MANUALLY LEVER OPERATED 1-1/2 & 3 TON LINK CHAIN HOIST

The **R-CH Series** 1-1/2 & 3 ton hoists promise to provide years of dependable service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The **R-CH Series** hoists feature a time tested and field proven ratchet & pawl design for transmission and distribution applications.

FEATURES:

Light weight, compact design that is simple to operate and easy to maintain.

Cast steel alloy construction provides unmatched resistance to shock and fatigue.

The Ratchet and Pawl Mechanism provides safe operation in which one pawl is always engaged during lifting and lowering operations.

May be rigged for use in lifting, pulling or binding applications from any position.

Minimal head & face room required for operation.

Safety hooks rotate 360° and feature spring latches to provide secure support and load connections.

Quickly remove slack by pulling the free chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control of the handle.

5 Foot Standard lift. *Custom lift lengths available.*

R-CH-3000

R-CH-6000

Manufactured to meet **ASME B30.21**

R-CH-3000	R-CH-6000
Capacity: 1-1/2 Ton	Capacity: 3 Ton
Approx Pull: 72 lbs.	Approx Pull: 75 lbs.
Handle: 17 in.	Handle: 17 in.
Head: 11 in.	Head: 15-7/8 in.
Stand. Lift: 55-1/2 in.	Stand. Lift: 54 in.
Weight: 15.25 lbs.	Weight: 21.25 lbs.



RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com