



RELIABLE EQUIPMENT & SERVICE CO., INC.

REL-35T-PNC

35 TON HYDRAULIC STEEL PUNCH



REL-35T-PNC

35 TON HYDRAULIC STEEL PUNCH

The **REL-35T-PNC** hydraulic punch was designed to punch holes through 1/2" aluminum, copper, and mild steel. The punched hole size is 1/16" larger than your bolt size. A stripper guide extends on either side of the ram to strip the material after punching. This portable hand-held unit will operate from any 10,000 psi hydraulic pumping source.

Applications include punching of bus bars, tower iron, railing, I-beams and truck frames.

The **REL-35T-PNC** comes complete with four sets of punch and die sizes for 3/8", 1/2", 5/8", and 3/4" bolts and carrying case.

NOTE: USE ONLY 10,000 psi RATED HOSE

Custom size punch and dies are available upon request. Oval and square sizes are also available. Consult factory for order information.

SPECIFICATIONS:

Output	35 ton
Weight	28 lbs.
Capacity	1/2" Thick Mild Steel
Max. Hole	13/16" Diameter
Dimensions	14" x 8" x 3.5"
Throat Depth	2.75"
Order Data:	
Model#	Description
REL-70P	Steel Punch w/ Female Coupler

ACCESSORIES

REL-716P	7/16 Punch & Die Set for 3/8" Bolt
REL-916P	9/16 Punch & Die Set for 1/2" Bolt
REL-1116P	11/16 Punch & Die Set for 5/8" Bolt
REL-1316P	13/16 Punch & Die Set for 3/4" Bolt



RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com