



# RELIABLE EQUIPMENT & SERVICE CO., INC.


Select the proper bushing as indicated by the cable chart. (Reference Code Name, Size, and Strand) *Right*  
NOTE: Check to ensure that bushing halves match.

1. Install the bushing halves completely into the hinged bushing holder. (R-ACSR-BH)
2. Place the bushing holder assembly around the cable with the exposed end of the bushing at the point to be trimmed.
3. Close the bushing holder by rotating the wing nut pin completely into the slotted seat and tighten. NOTE: If cable has spread or is out of round, rotate the holder slightly on cable, to ensure that the cable is seated properly in the holder.

4. Position the cutter onto the cable/holder by aligning both roller flanges with the guide groove of the bushing, and turning the feed knob until the blade contacts the cable.
5. Revolve cutter around cable while turning the feed knob. NOTE: The cutter wheel hub will STOP the blade advance slightly before the last strands are completely severed.
6. Retract the cutter wheel and remove cutter from the cable.
7. Carefully remove the partially severed strands by hand. **CAUTION: Cable ends may be SHARP.**
8. After trim cut, loosen wing nut, move bushing holder assembly back from trimmed end and retighten. This will secure the strands until the splice is complete.

## REL-ACSR-CT/CT-2 ACSR CABLE TRIMMER

### PARTS DRAWING #1



## REL-ACSR-CT/CT-2 ACSR CABLE TRIMMER PARTS LIST

1	R-CT-CS	TRIMMER CASE.....	1
2	R-CT-2	CUTTER FRAME.....	1
3	R-CT-3	CUTTER BAR.....	1
4	R-CT-4	FEED SCREW, MALE.....	1
5	R-CT-5	FEED SCREW, FEMALE.....	1
6	R-CT-6	KNOB.....	1
7	R-CT-7	WASHER.....	1
8	R-CT-8	SCREW.....	1
9	R-CT-9	CUTTER WHEEL (BLADE).....	1
	R-CT-20	CUTTER WHEEL (BLADE CT-2)...	1
10	R-CT-10	WHEEL SCREW.....	1
11	R-CT-11	ROLLER PIN.....	2
12	R-CT-12	ROLLER.....	2
13	R-CT-13	BUSHING HOLDER.....	1
14	R-CT-14	ROLL PIN.....	1
15	R-CT-15	PIN, SCREW.....	1
16	R-CT-16	WING NUT.....	1
17	R-CT-17	BAR.....	1
18	R-CT-18	SCREW, BUSHING.....	2
19	R-CT-19	RETAINER.....	2

## STANDARD BUSHINGS

BUSHING	CODE	AWG Cir. Mils	Strands
RE5900	RAVEN	1/0	6/1
RE5761	QUAIL	2/0	6/1
RE5762	PIGEON	3/0	6/1
RE5763	PENGUIN	4/0	6/1
RE5766	PARTRIDGE	266800	26/7
RE5768	MERLIN	336400	18/1
RE5769	LINNET	336400	26/7
RE5771	CHICKADEE	397500	18/1
RE5772	BRANT	397500	24/7
RE5773	IBIS	397500	26/7
RE5774	LARK	397500	30/7
RE5775	PELICAN	47700	18/1
RE5776	FLICKER	47700	24/7
RE5777	HAWK	47700	26/7
RE5780	PARAKEET	556500	24/7
RE5781	DOVE	556500	26/7
RE5789	GROSBEAK	636000	26/7
RE5800	DRAKE	795000	26/7
RE5801	MALLARD	795000	30/19
RE5805	RAIL	954000	45/7
RE5806	CARDINAL	954000	54/7
RE5815	PHEASANT	1272000	54/19
RE5824	CHUKAR	1780000	84/19

**New bushings will be added as required.**

If you do not see what you need in the list above, please contact **RELIABLE** at **800-966-3530**.