



# RELIABLE EQUIPMENT & SERVICE CO., INC.

## REL-PL-P

### Hydraulic Pole Puller

Operating Pressure 2,800 psi

**Includes:**

- Hydraulic Cylinder with Flush Face Coupler Set
- Swivel Chain Hook Assembly
- Chain (1/2" X 6' Alloy)
- Base Plate
- Back Plate

**Optional:**

- Pole Puller Pad

The REL-LP-P will make Pole Pulling with a boom a thing of the PAST.

Reduce boom damage and potential for injury related to pole pulling.

Simple installation and operation combined with RELIABLE performance will make the REL-PL-P (Pole Puller) a "Must Have Accessory" for all of your pole pulling operations.



## RELIABLE EQUIPMENT

301 Ivyland Road • Warminster, PA 18974  
Call: 215-357-3500 Fax: 215-357-9193  
On the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)

### SPECIFICATIONS

Operating Pressure:	2,800 psi
Recommended Flow:	4-8 gpm
Lift at Max. Pressure:	50,120 lbs.

Part	Wt.
Hydraulic Cylinder	57 lbs.
Base Plate	25 lbs.
Back Plate	7 lbs.
Swivel Chain Hook Assy.	36 lbs.
Chain (1/2" X 6' Alloy)	15 lbs.
Pad (optional)	25 lbs.