

RELIABLE EQUIPMENT & SERVICE CO., INC.

SPECIFICATIONS

Model	REL-18000H
Capacity:	18,000 lbs.
Travel:	60 inches
Headroom:	30 inches
Handle:	34 inches
Stroke:	52 inches
Weight:	120 lbs.



REL-18000H

MANUALLY LEVER OPERATED 9 TON ROLLER CHAIN HOIST

The **REL-H Series** hoists from **RELIABLE** promises to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-H Series** hoists utilizes a multiple chain configuration to offer increased capacity.

The chain lug hook may be detached to provide a longer lift capacity and faster operation in 4-1/2 ton applications.




**RELIABLE EQUIPMENT
& SERVICE CO., INC.**

301 Ivyland Road • Warminster, PA 18974

Phone: 800-966-3530 • Fax: 215-357-9193

Visit us on the web at www.Reliable-Equip.com





RELIABLE EQUIPMENT & SERVICE CO., INC.

SPECIFICATIONS

Model	REL-22000H
Capacity:	22,000 lbs.
Travel:	60 inches
Headroom:	30 inches
Handle:	34 inches
Stroke:	52 inches
Weight:	130 lbs.



REL-22000H

MANUALLY LEVER OPERATED 11 TON ROLLER CHAIN HOIST

The **REL-H Series** hoists from **RELIABLE** promises to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-H Series** hoists utilizes a multiple chain configuration to offer increased capacity.

The chain lug hook may be detached to provide a longer lift capacity and faster operation in 4-1/2 ton applications.



RELIABLE EQUIPMENT & SERVICE CO., INC.

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com



RELIABLE EQUIPMENT & SERVICE CO., INC.

SPECIFICATIONS

Model	REL-26000H
Capacity:	26,000 lbs.
Travel:	60 inches
Headroom:	30 inches
Handle:	34 inches
Stroke:	52 inches
Weight:	140 lbs.



REL-26000H

MANUALLY LEVER OPERATED 13 TON ROLLER CHAIN HOIST

The **REL-H Series** hoists from **RELIABLE** promises to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.


The **REL-H Series** hoists utilizes a multiple chain configuration to offer increased capacity.

The chain lug hook may be detached to provide a longer lift capacity and faster operation in 4-1/2 ton applications.



 **RELIABLE EQUIPMENT
& SERVICE CO., INC.**

301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com



RELIABLE EQUIPMENT & SERVICE CO., INC.

SPECIFICATIONS

Model	REL-30000H
Capacity:	30,000 lbs.
Travel:	60 inches
Headroom:	30 inches
Handle:	34 inches
Stroke:	52 inches
Weight:	153 lbs.



REL-30000H

MANUALLY LEVER OPERATED 15 TON ROLLER CHAIN HOIST

The **REL-H Series** hoists from **RELIABLE** promises to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-H Series** hoists utilizes a multiple chain configuration to offer increased capacity.

The chain lug hook may be detached to provide a longer lift capacity and faster operation in 4-1/2 ton applications.



301 Ivyland Road • Warminster, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com